

Pilot Burner

Low Pressure (PL 1) / High Pressure (PL 2)

Part No. 1117



SPECIFICATIONS

Model No.	Length	Diameter	Optimum Working Pressure	Consumption Per Hour	Rated Heat Output
PL-1	92 mm	16 mm	0.035 Kg/cm ²	0.043 Kg	480 kcal/hr
	3.62 ins	0.63 ins	0.50 psig	0.094 lbs	1,895 btu/hr
PL-2	92 mm	16 mm	0.3 Kg/cm ²	0.400 Kg	4500 kcal/hr
	3.62 ins	0.63 ins	4.50 psig	0.950 lbs	17,765 btu/hr

These burners could be manufactured for piped natural gas or LP gas.

Brass Adapters And Couplings

There are individual fittings for fixing on M.S. pipeline for obtaining different types of outlets and are used to connect valves regulators and any other fittings on to the pipeline.



Adapters In Forged Brass

Part No. 1131 to 1135

- 1/8" MT x MCV
- 1/4" MT x MCV
- 3/8" MT x MCV
- 1/2" MT x MCV
- 3/4" MT x MCV
- 1" MT x MCV



Couplings In Forged Brass / MS / SS

Part No. 1151 to 1159

- 1/8" MT x 1/4" CU
- 1/8" MT x 3/8" CU
- 1/4" MT x 3/8" CU
- 3/8" MT x 3/8" CU
- 3/8" BSPF x 1/4" MT
- 1/2" MT x 1/2" MT
- 1/2" MT x 3/8" CU
- 3/8" MT x 3/8" MT
- 1" MT x 3/8" MT
- 1" MT x 3/8" CU



Three way Tee in 3/8" m/f end connections

Part No. 1136